

Standard chemical pump

Type NCL

- Operation up to 250°C
- Wide range of variants
- Universally applicable





Type NCL

The type NCL is a standardized chemical pump PN 16 according to ISO 2858. Sizes deviating from the characteristic diagram and adapted to the requirements of the operators, it is graded in such a way that the best possible efficiency is achieved. This pump is a single-stage, single-entry volute casing pump in process design, with axial suction port and axial center discharge port pointing vertically upwards. In addition to the standard version, the NCL is also available with heating jacket, with inducer, with axle-centered suspension or as a version with open impeller as well as wear plate. Due to a wide range of materials and the possibility of installing various shaft sealing systems, DICKOW standardized chemical pumps are suitable for pumping almost all media used in the above mentioned industries.

Design

Volute casing pump
single-staged
Mechanical Seal
horizontal
no
Rolling bearing
Oil / Grease

Technical data

Q max	1400 m³/h**
H max	250 m**
Operating pressure	16/24/40 bar*
Temperature	250°C*
max rotational speed	3500 min ⁻¹

^{*} higher temperatures and pressures on request

Material

Ductile cast iron (EN-GJS) / Cast steel (GP 240 GH), Austenitic cast steel (1.4408 / 1.4571), Duplex (1.4517), Ni-based (2.4686)

Norm

ISO 2858 / ISO 15783

Explosion protection: Category 2 / Zone 1

More Information



^{**} depending on size and speed

Sectional view

















